

## 1103 Series - Wired Disabled WC & Accessible Alarm System

The versatile CAUK 1103 series system is simple to install and can be loop or star wired using good quality CAT5E cable.

It is designed to accommodate future changes in specification, expansion and new monitoring facilities. This system can be supplied as 'cancel at source' or 'cancel at the panel'.

This comprehensive wired system includes:

- A RS232 output to a separate pager transmitter. The location is transmitted and displayed on the pocket alphanumeric.
- The pager system range is between 800 to 1000 metres. Greater range is available.

Call Aid UK products are fully compliant with British Standards BS8300:2009. The British Standard requires all new disabled toilets to be fitted with an emergency toilet alarm.

Standard equipment to each WC will include:

- Ceiling mounted pull switch with two 'Triangle' pulls.
- Wall mounted Call/Reset point with one 'Triangle' pull.
- Over door lamp with integral sounder to attract attention.

There is a large range of CAUK products that can be used with this master receiver.

**Be advised: Avoid fitting CCA (copper clad aluminium) cable. It is not CAT5e compliant.**

### 1103 - Wired Disabled WC Alarm Indicator Panel

Receives calls & alerts from 50+ call units. When a call unit is pressed, the 1103 alphanumeric display will show the name of the room/user name that is calling. A high level sounder will be activated until the call is cancelled.

The master indicator panel can be wall or desk mounted.

Wall mounted units will require a stainless steel wall bracket.

The 1103 requires mains power via either:

12V Power Supply Unit

12V PSU With Standby Battery

Stainless steel wall bracket

Size (mm) 195 L x 151 W x 48 D

Desk P/No. A5183  
Wall P/No. A5185



P/No. A3684

P/No. A1871

P/No. A2752

# 1103 Series - Wired Disabled WC & Accessible Alarm System

## 1120 - Disabled Toilet Assist/Panic Unit

The 1120 wall unit can be fitted to toilets or other areas where the disabled are at risk. Pressing either red button or pulling the fitted pull cord will initiate an alarm.

Additional ceiling mounted pull switches can be added.

Supplied with an integrated pull cord & triangle

Size (mm): 86 L x 86 W x 12 D

Surface Mounted P/No. A4896  
 Wall Mounted P/No. A4898



## 1110 - Over Door Lamp + Buzzer

1110 Over Door Lamp is fitted over disabled toilet doors. The internal sounder attracts local attention. This unit is wired back to the 1120 button. Outdoor strobes/sounders are also available. Various LED colours are available.

Size (mm): 86L x 86 W x 68 D

Red Lens & Red LED Minus Buzzer	P/No. A3741 P/No. A5447
Clear Lens & Red LED Minus Buzzer	P/No. A4851 P/No. A5428
Amber LED	P/No. A5430
Green LED	P/No. A5429
Blue LED	P/No. A5431

## 1110 - Over Door Lamp (No Buzzer)

Size (mm): 86 L x 86 W x 60 D



## 1114 - Ceiling Mounted Pull Cord

This 1114 switch is used to provide additional cover in disabled toilets or other areas where the disabled are at risk. The ceiling mounted pull cord is wired back to the 1120 button. A clear lens is also available.

Red Lens P/No. A4174  
 Clear Lens P/No. A5454

